

IN THE CLAIMSRECEIVED
CENTRAL FAX CENTER

JAN 12 2007

1-43. (canceled)

44. (previously presented) A medical implant apparatus, comprising:

a receiver member having a longitudinal axis and defining an upper opening portion and a lower opening portion, a channel transverse to and communicating with said upper opening portion, and an interior groove in said member substantially perpendicular to said axis;

a retaining member having an inner dimension and an outer dimension, said retaining member occupying said groove; and

a longitudinal member at least partially within said channel.

45. (currently amended) The apparatus of claim 44, wherein said groove communicates with said lower opening portion of said receiver member.

46. (previously presented) The apparatus of claim 44, wherein said retaining member is a substantially circular ring member.

47. (previously presented) The apparatus of claim 44, wherein said retaining member is a substantially planar member.

48. (previously presented) The apparatus of claim 46, wherein said ring member includes a gap whereby said ring member can be contracted.

RESPONSE TO FINAL OFFICE ACTION
Application Ser. No. 10/731,210
Atty Dkt. No. 4002-3460/PC398.08
#439423

Page 2 of 14

49. (previously presented) The apparatus of claim 44, wherein when said retaining member is within said groove, said retaining member is substantially immovable in a radial direction.

50. (previously presented) The apparatus of claim 44, further comprising a bone anchor having a head within said receiver member, said head having a diameter larger than said inner dimension of said retaining member.

51. (previously presented) The apparatus of claim 50, wherein said head of said bone anchor is substantially between said retaining member and said upper opening portion.

52. (previously presented) The apparatus of claim 50, wherein said retaining member substantially surrounds a part of said bone anchor.

53. (previously presented) An apparatus for receiving and holding components of a multi-social bone anchor system, comprising:
a receiver member defining an upper opening portion and a lower opening portion, a channel transverse to and communicating with said upper opening portion and said lower opening portion, and a groove around at least a portion of said lower opening portion; and
a bone anchor member having a head at least partially within said lower opening portion.

54. (previously presented) The apparatus of claim 53, wherein said receiver member includes at least two branches defining said channel, said branches being internally threaded with reverse-angle threads.

RESPONSE TO FINAL OFFICE ACTION
Application Ser. No. 10/731,210
Any Dkt. No. 4002-3460/PC398.08
#439425

Page 3 of 14

55. (previously presented) The apparatus of claim 53, further comprising a longitudinal member at least partially within said channel.

56. (previously presented) The apparatus of claim 53, further comprising a closure member at least partially within said upper opening portion.

57. (previously presented) The apparatus of claim 56, wherein said closure member includes a set screw.

58. (previously presented) The apparatus of claim 57, wherein said receiver member includes internal reverse-angle threads, and said set screw included external threads capable of threadable mating with said reverse-angle threads.

59-62. (cancelled)

63. (new) The apparatus of claim 44, further comprising a fixation member having a head, said head being within said receiver member and a portion of said fixation member extending through said lower opening portion and out of said receiver member, wherein said retaining member is below said head.

64. (new) The apparatus of claim 44, further comprising a fixation member having a head, said head being within said receiver member and a portion of said fixation member extending

RESPONSE TO FINAL OFFICE ACTION
Application Ser. No. 10/731,210
Atty Dkt. No. 4002-3460/PC398.08
#439423

Page 4 of 14

through said lower opening portion and out of said receiver member, wherein said head contacts said retaining member when said apparatus is locked.

65. (new) The apparatus of claim 44, further comprising a fixation member having a head, said head being within said receiver member and a portion of said fixation member extending through said lower opening portion and out of said receiver member, wherein said head sits on said retaining member.

66. (new) The apparatus of claim 53, further comprising a fixation member having a head, said head being within said receiver member and a portion of said fixation member extending through said lower opening portion and out of said receiver member, wherein said retaining member is below said head.

67. (new) The apparatus of claim 53, further comprising a fixation member having a head, said head being within said receiver member and a portion of said fixation member extending through said lower opening portion and out of said receiver member, wherein said head contacts said retaining member when said apparatus is locked.

68. (new) The apparatus of claim 53, further comprising a fixation member having a head, said head being within said receiver member and a portion of said fixation member extending through said lower opening portion and out of said receiver member, wherein said head sits on said retaining member.

RESPONSE TO FINAL OFFICE ACTION
Application Ser. No. 10/731,210
Att'y Dkt. No. 4002-3460/PC398.08
#439425

Page 5 of 14